

# Natural Wood Noble Wood Oil Classic

## Product properties

Exclusive, weatherproof oil, that produces a glossy oil treatment. Contains UV filters that protect the wood from discolouration caused by the damaging rays of the sun. Prevents the formation of mould and mould growth on the surface.

- UV filter
- Exclusive
- Glossy



## Product use

Teak, mahogany and other precious woods, indoors and outdoors. For example, exterior doors and garage doors.

## Substrate

Must be absorbent, clean, dry, firm and suitable for surface treatment.

## Treatment

Wood stain, paint and decayed wood fibres should be totally cleaned by cleaning and sanding. Remove dirt, grime, grease and chalking materials by cleaning with Deck Cleaner. Algae, mould and mould growth are removed by cleaning with Façade Algae Remover. Sand uneven surfaces to a uniform finish.

## Application

Brush or roller.

Decide on your mode of application according to the desired finish.

Apply wet on wet, finish by brushing in the same direction.

Repeat the treatment until the wood is saturated, and appears uniform without the formation of a layer of varnish.

Cold/ heat can affect the viscosity of the material.

Condensation must be prevented during drying/curing.

Cold and increased humidity extends drying time, full curing and recoating interval.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

Always test adhesion and result before hanging.

## Expected result

Colourless and glossy surfaces that highlight the grain of the wood.

Expected durability 1 year.

The durability of the surface depends on the quality of the wood, construction, method and quality of the work and exposure.

The expected durability can therefore be shorter or longer than stated.

# Environmental information

Remove as much paint from tools as possible before cleaning.  
Bring remains of fluent paint to the local recycling centre.  
Minimize your paint waste by pre-estimating how much paint you need.  
Keep the leftover paint for future use so you can effectively reduce the environmental impact.

**Storage:** Cool, frost-free, and tightly closed

**Protection equipment:** Painting: eye protection, gloves. Sanding: respiratory protection.

## Technical Data

Product Type	Wood Oil
Gloss	Gloss;90
Density (kgs/l)	0.92
Solids Weight %	57
Solids Vol. %	50
Nominal spreading rate (m <sup>2</sup> /ltr.)	10
Min. working temp. during application and drying/curing	Min. +5°C
Humidity	Maximum atmospheric humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	4
Recoatable at 20° C, 60 % RH (Hours)	12
Fully cured at 20° C, 60 % RH (Days)	28
Dilution	White spirit
Cleaning of Tools etc.	Brush Cleaner

### Current TDS Version

March 2024

### Replaces TDS Version

July 2022