

Special Primer

Product properties

Extra rich priming paint that produces a matt surface. Ensures a uniform, saturated and filled bottom that is suitable for finishing with ceiling or wall paint in the desired quality.

- Priming paint
- Extra rich
- Matt



Product use

Priming paint of plaster, concrete, cardboard-coated gypsum board and filled surfaces before painting with ceiling and wall paint.

Also used for priming painting of glass felt, glass tissue and fiber felt.

Substrate

Must be clean, dry, firm and suitable for surface treatment.

Treatment

Remove loose material and paint by cleaning and sanding.

Remove dirt, grime, grease and chalking materials by cleaning with Fluren 37.

Water-soluble discolouration, nicotine and soot can be cleaned with Fluren 49.

Sand surface to matt finish as required.

Cracks, unevenness and holes must be filled.

Absorbent and porous substrates must be primed with Flügger Sealer.

Application

Brush, roller or spray.

Decide your choice of tool/utensil depending on the finish.

Apply wet on wet and finish by brushing/rolling in the same direction.

Cold/heat can affect the viscosity of the material.

Material temperature for spray painting, min. 12°C.

Condensation during drying/curing must not occur.

Cold and increased humidity extends drying time, full curing and recoat interval.

Increased temperature and low atmospheric humidity reduce drying time and full curing.

Always perform a test treatment for a check and acceptance of adhesion and result.

Expected result

Matt, covered surface.

Finish treat with paint in desired gloss and colour.

Environmental information

Minimize your paint waste by pre-estimating how much paint you need.

Remove as much paint as possible from tools before cleaning.

Paint and cleaning fluid must not be poured down drains, but collected and disposed of as environmental waste.

Empty and dry packaging should be sorted as plastic, metal handles should be removed and sorted as metal.

Store excess paint correctly so that leftovers can be used and environmental impact is minimised.

Storage

Cool, frost-free, and tightly closed

Protection equipment

Protect skin and eyes from splashes with suitable clothing, gloves and glasses.

Avoid inhalation of spray mist and grinding dust.

Wear suitable protective equipment, see safety data sheet for further information.

Supplementary Info

For this product there is issued an: [Environmental Product Declaration](#)

Technical Data

Product Type	Priming paint
Gloss	Matte
Density (kgs/l)	1.44
Solids Weight %	64
Solids Vol. %	49
Nominal spreading rate (m ² /ltr.)	8
Min. working temp. during application and drying/curing	Min. +10°C
Humidity	Max. humidity 80 % RH.
Drying time at 20° C, 60 % RH (Hours)	1
Recoatable at 20° C, 60 % RH (Hours)	4
Fully cured at 20° C, 60 % RH (Days)	28
Emission acc. to ISO 16000-9:2011 (< µg/m ² h after 28 days)	20
Dilution	Water. May be diluted 5-10 % at spraying.
Cleaning of Tools etc.	Water

Current TDS Version

October 2024

Replaces TDS Version

September 2024

